Appln. No. 10/035,066

Attorney Docket No. 10541-870

III. Listing of Claims

Claims 1-15 (Cancelled)

16. (Currently Amended): A laser-welded driveshaft comprising:

a tube having a driveshaft wall extending to an open end, the wall having

inner and outer surfaces; and

a yoke Nd:YAG laser-welded to the open end of the tube, the yoke having a

body portion and a tube-engaging pilot extending from the body portion, the body

portion having a head and an outer wall extending therefrom to the tube-engaging

pilot, the pilot having a contact wall extending from the outer wall defining an outer

shoulder to engage the open end of the tube, the contact wall being radially formed

to insert through the open end and engage the inner surface of the driveshaft wall to

press fit into the tube. tube;

a Nd:YAG laser-welded material located proximal to the outer shoulder and to

the open end of the tube.

17. (Currently Amended): The laser-welded driveshaft of claim 16 wherein

the driveshaft comprises [[the]] a metal alloy.

18. (Original): The laser-welded driveshaft of claim 17 wherein the metal

alloy is aluminum alloy.

19. (Currently Amended): The laser-welded driveshaft of claim 16 wherein

the driveshaft is configured to have a balance less than 0.2 [[in-oz]] oz-in balance.

-4-

Appln. No. 10/035,066

Attorney Docket No. 10541-870

20. (Cancelled)

21. (New) A laser-welded driveshaft comprising:

a tube having a driveshaft wall extending to an open end, the wall having

inner and outer surfaces; and

a yoke having a body portion and a tube-engaging pilot extending from the

body portion, the body portion having a head and an outer wall extending therefrom

to the tube-engaging pilot, the pilot having a contact wall extending from the outer

wall defining an outer shoulder to engage the open end of the tube, the contact wall

being radially formed to insert through the open end and engage the inner surface of

the driveshaft wall to press fit into the tube;

a laser-welded material located proximal to the outer shoulder and to the open

end of the tube.

22. (New): The laser-welded driveshaft of claim 21 wherein the driveshaft

comprises a metal alloy.

23. (New): The laser-welded driveshaft of claim 22 wherein the metal alloy

is aluminum alloy.

24. (New): The laser-welded driveshaft of claim 21 wherein the driveshaft

is configured to have a balance less than 0.2 oz-in balance.

-5-